

## High Solids Tint for Base-IC

B-TINT is a high solids pigment pack to be used specifically with the BASE-IC line of polyurea products. Available in 14 standard colors. One 32 oz tint pack is to be used with each 3-gallon kit of BASE-IC. Excessive amounts of tint can cause pigment float and an uneven colored coating. Adding Tint Packs will not alter the pot life or cure time of the coating.

### Typical Uses:

For Solid color base coats used in Industrial, Commercial, and Residential applications such as:

- **Schools and Universities**
- **Residential Garages and Basements**
- **Manufacturing and Warehouse Floors**
- **Retail, Restaurants and Hospitality**
- **Healthcare and Medical Offices**

14 Standard Colors  
Solid Opaque Coverage

Packaging:  
32 Ounce Pigment Packs

### Product Advantages:

- **Ultra-Fine Pigment for Easy Dispersion**
- **Field Packs to Reduce Waste**
- **Economical**
- **Portioned for Addition 3-gallon Kits**

### Coverage:

32 oz of B-TINT should be added to Part A of a 3-Gallon kit of BASE-IC. Test an area first to make sure coverage is adequate.

### Mixing Instructions:

Always mix or shake Base-IC Tint colorant prior to use. Add the entire 32-ounce contents to 2 gallons Part A and mechanically mix slowly for 2 minutes using a Jiffy-style mixer. When ready, add colored Part A to Part B and mechanically mix for 3 minutes before applying to the surface. Material may settle over time, re-mix as needed.

### Clean Up:

Clean tools with Xylene

**FOR PROFESSIONAL USE ONLY**

# Technical Data Sheet

## Storage:

Store in well-ventilated place. Keep Cool. Keep container tightly closed. Store locked up.

## Disposal:

Disposal of product and packaging should be in accordance with applicable regional, national and local laws and regulations.

## Shelf Life:

Up to one year from original manufacture date when stored in its original, unopened container at room temperature.

## Limitations:

This product is not intended for public use and is intended for use by qualified contractors and installers with proper experience and training in the use of these products, and that have read the complete safety data sheet. Apply product only when substrate and ambient temperatures are within the accepted range and to substrates that are a minimum of five degrees above dew point and will remain so during product cure. During application and cure protect product from all contaminants and traffic.

## Warranty:

Durável warrants our products to be of uniform quality, free from defects within manufacturing tolerances, and to conform to published specifications as of the date of sale. Durável has no control over the use of the product and therefore no warranty, expressed or implied, is made or can be made as to the application of the product or the results of use. The manufacturer's obligations shall be limited to refunding the purchase price or providing replacement product for material proven to be defective. Ninety days after delivery of product all warranty and other duties with respect to the quality of the product delivered shall be presumed to have been conclusively satisfied, all liability therefore terminates, and no action for breach of any stated or implied duties may thereafter be commenced. The end user is responsible for determining the product's suitability and assumes all risks and liabilities. Under no circumstances will Durável be subject to or held liable for a consequential damage to anyone in excess of the purchase price of the product.

## Disclaimer:

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável

# Technical Data Sheet

assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

## Safety Instructions:

Highly flammable. Suspected of Causing Cancer. Toxic to Aquatic Life with Long Lasting Effects. Causes Serious Eye Irritation. May Cause Respiratory Irritation. May Cause Drowsiness or Dizziness. May be Harmful if Swallowed. May be Harmful if Swallowed and Enters Airways. Causes Skin Irritation.

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating / lighting/ equipment. Use only non-sparking tools. Take action to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

### First Aid:

IF exposed or concerned: Get medical advice/attention

**IF ON SKIN:** (or hair) Take off immediately all contaminated clothing and wash before reuse. Rinse skin with water/ shower. If skin irritation occurs: Get medical advice or attention.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contacts, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

**IF SWALLOWED:** Immediately call a POISON CONTROL CENTER/doctor. Do NOT induce vomiting.

**PROP65 WARNING:** This product contains chemicals known to the state of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



**Always Review SDS & Technical Data Prior to Use**