

## Colorless Bubble Gum Stamp Release

Liquid Release is a clear colorless release agent for use with concrete stamps and texture tools. The bubble gum scented liquid creates a lubricating barrier that prevents concrete from adhering to tools and extends the life of stamps and skins. Liquid Release leaves no residues as it evaporates reducing clean up labor cost.

### Typical Uses:

- Freshly Placed Stamped Concrete
- Concrete Stencils
- Vertical Stamped Concrete

### Product Advantages:

- Pleasant Bubble Gum Scent
- Long Dwell Time
- Slow Evaporation
- Leaves No Residue

Dry Time – 1 to 2 hours

Application Temperature:  
50° to 80° F

Packaging:  
5-gallon pails  
1-gallon jugs

### Coverage:

Typically, 150-200 square feet per gallon, varies with surface porosity, texture and environmental conditions.

### Directions for Use:

### Application Instructions:

Apply in a mist by pump up sprayer on texture tools and the concrete surface, coating the surface as you work across the field. Clean tools with soap and water when done.

### Clean Up:

Water and detergent.

### Storage:

Store in well-ventilated place. Keep Cool. Keep container tightly closed. Store locked up.

**FOR PROFESSIONAL USE ONLY**

**PERFORMANCE COATINGS**

**Technical Data**

# Technical Data Sheet

## Disposal:

Disposal of product and packaging should be in accordance with applicable regional, national and local laws and regulations.

## Shelf Life:

Up to one year from original manufacture date when stored in its original, unopened container at room temperature.

## Limitations:

This product is not intended for public use and is intended for use by qualified contractors and installers with proper experience and training in the use of these products, and that have read the complete safety data sheet. Apply product only when substrate and ambient temperatures are within the accepted range and to substrates that are a minimum of five degrees above dew point and will remain so during product cure. During application and cure protect product from all contaminants and traffic.

## Warranty:

Durável warrants our products to be of uniform quality, free from defects within manufacturing tolerances, and to conform to published specifications as of the date of sale. Durável has no control over the use of the product and therefore no warranty, expressed or implied, is made or can be made as to the application of the product or the results of use. The manufacturer's obligations shall be limited to refunding the purchase price or providing replacement product for material proven to be defective. Ninety days after delivery of product all warranty and other duties with respect to the quality of the product delivered shall be presumed to have been conclusively satisfied, all liability therefore terminates, and no action for breach of any stated or implied duties may thereafter be commenced. The end user is responsible for determining the product's suitability and assumes all risks and liabilities. Under no circumstances will Durável be subject to or held liable for a consequential damage to anyone in excess of the purchase price of the product.

## Disclaimer:

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

# Technical Data Sheet

## Safety Instructions:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/ sparks/ open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take action to prevent static discharges. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Wash face, hands and any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection.

IF exposed or concerned: Get medical advice/attention.

**IF ON SKIN:** (or hair) Take off immediately all contaminated clothing. Rinse skin with water/ shower. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash before reuse.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contacts, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

**IF SWALLOWED:** Immediately call a POISON CONTROL CENTER/doctor. Do NOT induce vomiting. In case of fire use "alcohol resistant" foam, dry chemical, halon or carbon dioxide to extinguish. Collect spillage



**Always Review SDS & Technical Data Prior to Use**

REV.12.16.2020