DURÁVEL®
Products for Professionals

Restore-A-Seal™

Solvent Blend to Restore Acrylic Sealers

SURFACE PREPARATION

Technical Data

Restore-A-Seal is a strong blend of solvents and surfactants used to refresh old, faded solvent-based acrylic sealers. It helps soften and re-flow old sealer so dull, cloudy, or worn-looking surfaces can look fresh again. Restore-A-Seal penetrates through the sealer layers and helps the acrylic soak back into the concrete. It can also help remove trapped moisture and reduce blushing.

Restore-A-Seal may also be used before resealing. Some older acrylic sealers become hard and brittle after exposure to weather. Applying Restore-A-Seal before a new sealer coat helps soften the existing acrylic. This allows the new sealer to bond better and can improve the service life of the finished surface.

Typical Uses:

- **Stamped and Decorative Concrete**
- **Stained Concrete**
- **Exposed Aggregate**
- **Prior to Re-Sealing**

For Use on Solvent-Based Sealers Only

Substrate Temperature – 40° to 80° F

VOC Content - <100 g/L

Packaging:
1-Gallon Cans | 5-Gallon Pails

Product Advantages :

- **Removes Trapped Moisture**
- **Pure Solvents, Zero Solids**
- **Works at Lower Temperatures**
- **Alternative to Stripping Old Coating**
- **Works Faster than Xylene**

Coverage:

Typical application rate 150-250 sq ft per gallon. Especially thick coatings may require multiple applications.

Directions for Use:

Substrate Preparation:

Environmental Conditions: Do not apply if rain is expected within 24 hours after application. Water on the surface or high humidity may cause poor or unwanted results.

Apply the product when the surface temperature is between 40°F and 80°F. The surface temperature must also be at least 5°F above the dew point before application.

Mixing Instructions:

Material should be stirred well prior to application. Long term storage may allow material to separate.

FOR PROFESSIONAL USE ONLY

Application Instructions:

Clean the surface thoroughly with soap and water before applying Restore-A-Seal.

For best results, apply during the cooler part of the day. Cooler conditions allow the product to stay wet longer and work more effectively. Apply Restore-A-Seal with a pump-up sprayer that is resistant to xylene, or use a solvent-resistant paint roller. Apply the product evenly across the surface. Use enough material to completely re-wet the existing sealer all the way down to the bottom layer. Rolling or agitating the wet surface can help soften the old sealer faster. If needed, repeat the process after the sealer becomes hard enough to walk on.

Allow the sealer to dry at least 24 hours before allowing foot traffic, and at least 48 hours before heavy traffic. When using Restore-A-Seal before resealing, wait until the surface is hard enough to walk on before applying the new sealer. Wait times will vary depending on temperature. In most cases, the new sealer should be applied no sooner than 2 hours and no later than 6 hours after treating the surface with Restore-A-Seal.

Slip Resistance Disclaimer:

Notice: The Occupational Safety and Health Administration (OSHA) and the American Disabilities Act (ADA) have set enforceable standards for slip-fall protection on walking surfaces. The ADA standards are the more stringent and require a minimum coefficient of friction (CoF) on level walking surfaces of 0.6 and on ramped walking surfaces of 0.8. The system applicator/ end user assumes all responsibility to provide a flooring system that meets all current safety standards. Neither Durável nor its selling agents will be responsible for any injury that may be incurred in a slip-fall accident. Furthermore, Durável recommends the use of slip-resistant aggregate in all coatings or floor systems that could possibly be exposed to wet conditions or become contaminated with oils, grease, or other potential lubricants.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Protect from temperature extremes.

Disposal:

Recycle and/or dispose of contents and containers in accordance with local, regional, national, and international regulations.

Shelf Life:

Up to one year from original manufacture date when stored in its original, unopened container at room temperature. May be extended with reasonable care.

Limitations:

This product is not intended for public use and is intended for use by qualified contractors and installers with proper experience and training in the use of these products, and that have read the complete safety data sheet. Apply product only when substrate and ambient temperatures are within the accepted range.

Warranty:

IMPORTANT!

Before using any Durável product, read and understand its accompanying Safety Data Sheet & Application Instructions for important safety information.

STANDARD TERMS AND CONDITIONS OF SALE, INCLUDING STANDARD WARRANTY APPLY – VISIT Durável.com FOR THE LATEST VERSION.

Disclaimer:

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

Safety Instructions:

For Professional Use Only

Keep Out of Reach of Children and Animals

Highly Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposures.

Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Wash hands and arms thoroughly after handling. Do not touch eyes. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.

IF SWALLOWED: Get emergency medical help immediately. IF ON SKIN: wash with plenty of water and soap. IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If exposed or concerned, get medical advice. Get medical help if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical help. If eye irritation persists: Get medical help. Take off immediately all contaminated clothing and wash it before reuse.

In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish.

PROP65 WARNING: This product contains chemicals known to the state of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Always Review SDS & Technical Data Prior to Use