

Pigment for USB Polyurethane

USB-TINT is high solids pigment to be used specifically with USB solvent-base polyurethane. 14 standard colors are available. Adding USB-Tint will not alter the pot life or cure time of the polyurethane.

Typical Uses:

For Solid color finish coats used in Industrial, Commercial, and Residential applications such as:

- **Residential or Commercial Garages**
- **Warehouse and Office Spaces**
- **Manufacturing and Workshops**
- **Laboratories**
- **Aircraft Hangers**

Product Advantages:

- **Ultra Fine Pigment for Easy Dispersion**
- **Field Packs to Reduce Waste**
- **Economical for Solid Color Applications**
- **UV Stable Pigment**

Coverage:

Solid Opaque Coverage. Add nine ounces pigment per gallon of polyurethane.

Directions for Use:

Mixing Instructions:

If less than full kits will be mixed, each component should be mixed thoroughly with individual tools. Using the same tool to mix part A and Part B will cause contamination and ruin the material being saved for future use. UWB is to be mixed at a ratio of 4 parts A to 1 part B. In clean measuring containers pour the correct ratio in and mechanically mix for 3 minutes. **DO NOT USE A STIR STICK!** The amount of material mixed should only be what can be utilized within the pot life recommendations of the product. A jiffy style mixing paddle is recommended to limit the introduction of air while combining Part A and Part B.

Colors:

Light Gray	Pecan
Medium Gray	Khaki
Dark Gray	Ash White
Charcoal	Brick Red
Sun Buff	Maroon
Tan	Black
Taupe	White

Packaging:

32 Oz Pigment Packs

FOR PROFESSIONAL USE ONLY

Technical Data Sheet

Clean Up:

Xylene

Storage:

Store in well-ventilated place. Keep Cool. Keep container tightly closed. Store locked up.

Disposal:

Disposal of product and packaging should be in accordance with applicable regional, national and local laws and regulations.

Shelf Life:

Up to one year from original manufacture date when stored in its original, unopened container at room temperature.

Limitations:

This product is not intended for public use and is intended for use by qualified contractors and installers with proper experience and training in the use of these products, and that have read the complete safety data sheet. Apply product only when substrate and ambient temperatures are within the accepted range and to substrates that are a minimum of five degrees above dew point and will remain so during product cure. During application and cure protect product from all contaminants and traffic.

Warranty:

Durável warrants our products to be of uniform quality, free from defects within manufacturing tolerances, and to conform to published specifications as of the date of sale. Durável has no control over the use of the product and therefore no warranty, expressed or implied, is made or can be made as to the application of the product or the results of use. The manufacturer's obligations shall be limited to refunding the purchase price or providing replacement product for material proven to be defective. Ninety days after delivery of product all warranty and other duties with respect to the quality of the product delivered shall be presumed to have been conclusively satisfied, all liability therefore terminates, and no action for breach of any stated or implied duties may thereafter be commenced. The end user is responsible for determining the product's suitability and assumes all risks and liabilities. Under no circumstances will Durável be subject to or held liable for a consequential damage to anyone in excess of the purchase price of the product.

Disclaimer:

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use,

Technical Data Sheet

processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

Safety Instructions:

Highly Flammable. Suspected of Causing Cancer. Toxic to Aquatic Life with Long Lasting Effects. Causes Serious Eye Irritation. May Cause Respiratory Irritation. May Cause Drowsiness or Dizziness. May be Harmful if Swallowed. May be Harmful if Swallowed and Enters Airways. Causes Skin Irritation. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take action to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

IF exposed or concerned: Get medical advice/attention.

IF ON SKIN: (or hair) Take off immediately all contaminated clothing. Rinse skin with water/ shower

If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contacts, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

IF SWALLOWED: Immediately call a POISON CONTROL CENTER/doctor. Do NOT induce vomiting.

In case of fire use, "alcohol resistant" foam, dry chemical, halon or carbon dioxide to extinguish.

Collect spillage.

PROP65 WARNING: This product contains chemicals known to the state of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



Always Review SDS & Technical Data Prior to Use

REV.1.4.2021