

Pigment for UWB-Gloss Polyurethane

UWB-TINT is high solids pigment to be used specifically with UWB-Gloss polyurethane. Available in six colors. Adding UWB-Tint will not alter the pot life or cure time of the polyurethane.

Typical Uses:

For Solid color finish coats used in Industrial, Commercial, and Residential applications such as:

- **Residential or Commercial Garages**
- **Warehouse and Office Spaces**
- **Manufacturing and Workshops**
- **Laboratories**
- **Aircraft Hangers**

Product Advantages:

- **Ultra Fine Pigment for Easy Dispersion**
- **Field Packs to Reduce Waste**
- **Economical for Solid Color Applications**
- **UV Stable and Chemically Resistant**
- **Low Oder**

Coverage:

Solid Opaque Coverage. Add 16 oz pigment per 1.25-gallon kit of UWB-Gloss.

Directions for Use:

Mixing Instructions:

Always mix or mechanically shake UWB-Tint colorant prior to blending in resin. Add UWB-Tint to Part A of UWB-Gloss polyurethane and mechanically mix slowly for 2 minutes using a Jiffy-style mixer. When ready, mechanically mix the colored Part A with Part B for 3 minutes before applying to the surface.

Clean Up:

Warm water and detergent.

Colors:

Light Gray
Medium Gray
Khaki
Sun Buff
White
Black

Packaging:

32 Oz Pigment Packs

FOR PROFESSIONAL USE ONLY

Technical Data Sheet

Storage:

Store in well-ventilated place. Keep Cool. Keep container tightly closed. Store locked up.

Disposal:

Disposal of product and packaging should be in accordance with applicable regional, national and local laws and regulations.

Shelf Life:

Up to one year from original manufacture date when stored in its original, unopened container at room temperature.

Limitations:

This product is not intended for public use and is intended for use by qualified contractors and installers with proper experience and training in the use of these products, and that have read the complete safety data sheet. Apply product only when substrate and ambient temperatures are within the accepted range and to substrates that are a minimum of five degrees above dew point and will remain so during product cure. During application and cure protect product from all contaminants and traffic.

Warranty:

Durável warrants our products to be of uniform quality, free from defects within manufacturing tolerances, and to conform to published specifications as of the date of sale. Durável has no control over the use of the product and therefore no warranty, expressed or implied, is made or can be made as to the application of the product or the results of use. The manufacturer's obligations shall be limited to refunding the purchase price or providing replacement product for material proven to be defective. Ninety days after delivery of product all warranty and other duties with respect to the quality of the product delivered shall be presumed to have been conclusively satisfied, all liability therefore terminates, and no action for breach of any stated or implied duties may thereafter be commenced. The end user is responsible for determining the product's suitability and assumes all risks and liabilities. Under no circumstances will Durável be subject to or held liable for a consequential damage to anyone in excess of the purchase price of the product.

Disclaimer:

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável

Technical Data Sheet

assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

Safety Instructions:

Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contacts, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention

IF SWALLOWED: Immediately call a POISON CONTROL CENTER/doctor

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice or attention.

Take off contaminated clothing and wash before reuse

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.



Always Review SDS & Technical Data Prior to Use