

Solvent Blend To Restore Acrylic Sealers

Restore-A-Seal contains a strong blend of key solvents and surfactants designed to emulsify and re-flow old tired solvent-based acrylic sealers. Thick layers of old sealer with a dingy faded look are made fresh again. Restore-A-Seal penetrates down through the deepest layers of sealer to help the acrylics soak back into the concrete substrate, remove trapped moisture and eliminate blushing.

Typical Uses:

Unique formula used in Industrial, Commercial, and Residential applications such as:

- **Stamped Concrete**
- **Overlay Products**
- **Stained Concrete**
- **Exposed Aggregate**
- **Broom Finish Concrete**

Product Advantages:

- **Removes trapped moisture**
- **Pure Solvents**
- **Works at lower temperatures**
- **Clear non-yellowing formula**

Coverage:

First Application: 150 – 250 sq ft per gallon
Second Application: 225 – 350 sq ft per gallon

Coverage rates will vary greatly depending on how many layers of sealer need to be emulsified, application method, and original surface porosity.

Storage:

Store in well-ventilated place. Keep Cool. Keep container tightly closed. Store locked up.

Shelf Life:

Up to one year from original manufacture date when stored in its original, unopened container at room temperature.

Directions for Use:

Substrate Preparation:

ENVIRONMENTAL CONDITIONS: Rain should not be forecast for 24 hours after application. Water present on the surface or high humidity may not produce the desired effects. Product should be placed between 40° – 80° F surface temperature. Ambient temperature should not be used to judge application temperature. Ambient temperature is an indicator, but surface temperature must be considered during application and curing of the product. Use of a laser temperature gauge is necessary to find the substrate temperature.

For Use on Solvent-Based Sealers Only

Dry Time, Tack Free – 30 to 60 minutes
Dry Time, Foot Traffic – 4 to 6 hours
Dry Time, Heavy Traffic – 24 to 48 hours
Recoat Interval – 4 to 24 hours
Application Temperature – 40° to 80° F
VOC Content – < 100 g/L

PACKAGING

1-Gallon Cans
5-Gallon Pails

FOR PROFESSIONAL USE ONLY

Technical Data Sheet

SUBSTRATE PREPERATION CONTINUED:

If product is applied outside of these temperature parameters, the product that Restore-A-Seal is used on may not cure properly and will not meet specifications in hardness or chemical resistance. Temperature should also be maintained during the curing process to avoid later issues.

Mixing Instructions:

Material should be stirred well prior to application. Long term storage may allow material to separate.

Application Instructions:

Apply using a solvent-resistant sprayer designed for this use. Restore-A-Seal may also be rolled using a 1/2" or 3/4" nap roller. Solvent should be applied evenly to the surface and allowed to breakdown the existing sealer. Use enough product to completely re-wet the existing sealer through to the bottom layer. A second treatment may be applied 4 to 24 hours later with the same methods if needed. Allow the sealer 24 hours to dry before returning to foot traffic, 48 hours to heavy traffic.

Maintenance:

Use walk-off mats at entrances to keep the floor free of sand and abrasives to minimize scratching. Apply protective felt pads to furniture and fixtures prior to placing on the coating. Use a pH-balanced cleaner to remove light soils. A dilution of ammonia and water will clean most contaminants off the surface. Spills should be cleaned promptly to prevent long term staining. Citric based cleaners should not be used.

Clean Up:

Clean tools with Xylene

Slip Resistance Disclaimer:

Notice: The Occupational Safety and Health Administration (OSHA) and the American Disabilities Act (ADA) have set enforceable standards for slip-fall protection on walking surfaces. The ADA standards are the more stringent and require a minimum coefficient of friction (CoF) on level walking surfaces of 0.6 and on ramped walking surfaces of 0.8. The system applicator / end user assumes all responsibility to provide a flooring system that meets all current safety standards. Neither Durável nor its selling agents will be responsible for any injury that may be incurred in a slip-fall accident. Furthermore, Durável recommends the use of slip-resistant aggregate in all coatings or floor systems that could possibly be exposed to wet conditions or become contaminated with oils, grease or other lubricants. Refer to the technical data sheet on acrylic wax floor finishes that meet requirements for ASTM D2047.

Limitations:

This product is not intended for public use and is intended for use by qualified contractors and installers with proper experience and training in the use of these products, and that have read the complete safety data sheet. Apply product only when substrate and ambient temperatures are within the accepted range and to substrates that are a minimum of five degrees above dew point and will remain so during product cure. During application and cure protect product from all contaminants and traffic.

Disposal:

Disposal of product and packaging should be in accordance with applicable regional, national and local laws and regulations.

Technical Data Sheet

Warranty:

Durável warrants our products to be of uniform quality, free from defects within manufacturing tolerances, and to conform to published specifications as of the date of sale. Durável has no control over the use of the product and therefore no warranty, expressed or implied, is made or can be made as to the application of the product or the results of use. The manufacturer's obligations shall be limited to refunding the purchase price or providing replacement product for material proven to be defective. Ninety days after delivery of product all warranty and other duties with respect to the quality of the product delivered shall be presumed to have been conclusively satisfied, all liability therefore terminates, and no action for breach of any stated or implied duties may thereafter be commenced. The end user is responsible for determining the product's suitability and assumes all risks and liabilities. Under no circumstances will Durável be subject to or held liable for a consequential damage to anyone in excess of the purchase price of the product.

Disclaimer:

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

Safety Instructions:

Use with adequate ventilation to ensure exposure levels are maintained below the limits provided on the product Safety Data Sheet. Use local exhaust ventilation to control airborne vapor. Ensure eyewash/safety shower stations are available near areas where this product is used. As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing vapors/mists generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

First Aid:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF ON SKIN: (or hair) Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.

IF SWALLOWED: If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or SDS with the victim to the health professional.

Always Review SDS & Technical Data Prior to Use.